



# Lashing Wire Datasheet

Bekaert Lashing wire provides flexibility, strength, and corrosion resistance required for supporting fiber optic cables in Outside Plant (OSP) telecommunications projects. The product meets the requirements per ASTM A580 and works with most cable lashers.



## Specifications, per ASTM A580

AISI Grade	UNS	W.Nr	Wire Diameter (in)	Weight per coil (lb)	Length per coil (lb)	Average break strength (lb)	Coils per box	Approx. shipping weight per box (lb)
430SS	S43000	1.4016	0.045	6.5	1,200	125	6	40
302SS	S302000	1.4310	0.038	6.3	1,600	115	6	38
302SS	S302000	1.4310	0.045	6.5	1,200	165	6	40
316SS	S31600	1.4401	0.045	6.5	1,200	165	6	40
316SS	S31600	1.4401	0.038	6.3	1,600	115	6	38

## Pack specifications

### Coil Dimensions

ID	1 5/8" min
OD	5 3/8" max
Height	2" max

### Box Dimensions

Coils per box	6
Width	5 1/2"
Length	11"
Height	5 1/2"

### Box Dimensions

Boxes per box	63
Width	33"
Length	42"
Height	26"

Finish: Bright annealed

ISO 9001:2015 certified



Contact us

More Information?

4300 Wildwood Parkway,  
Suite 100  
Marietta, Georgia 30339, USA  
770.514.2219  
[www.bekaert.com/power-utilities](http://www.bekaert.com/power-utilities)

Modifications reserved.  
All details describe our products in general form only. For ordering and design only use official specifications and documents. Unless otherwise indicated, all trademarks mentioned in this brochure are registered trademarks of NV Bekaert SA or its subsidiaries. ©Bekaert 2022